

PCE Group Europe [®]

www.pce-group-europe.com

DIN EN ISO 9001

Incredible scales

- Weighing ranges: 60 kg & 150 kg
- High Resolution: 10 g & 20 g
- Large Display, 35 mm
- Internal rechargeable battery & Mains power adapter
- RS-232 interface
- Tare- / Data-Hold- / Alarm-Function
- Stainless steel pan (460 x 560 mm)
- Calibration certificate available (Option)



PCE-TS Series

Platform Scales

Platform Scale PCE-TS Series

The PCE-TS is a multi-purpose industrial platform scale. This industrial platform scale displays the weighing units in either kilograms (kg) or pounds (lb) to provide accurate weighing results at an affordable price. The scale works on battery or AC power providing you with total weighing flexibility. Versatile PCE platform scale is used for weighing applications for shipping and receiving, manufacturing & general purpose weighing. This scale increments in 0.01 kg graduations and the stainless steel platform is removable for easy cleaning. The indicator is also in a stainless steel housing with a splash proof keyboard. The indicator mounted on a stainless steel pillar has a large and easy to read LCD display. These scales are designed to perform routine weighing operations with speed, precision and reliability. The indicator features a large high LCD for easy viewing along with RS-232 interface for connection to a PC. The optional software-kit allows data transfer to a PC. The indicator can be placed up to 1.5 m away from the base when fully stretched. Low profile design allows cartons to slide easily onto the platform.

Scale model	PCE-TS 60	PCE-TS 150
Maximum capacity	60 kg	150 kg
Readability	10 g	20 g
Linearity	±20 g	±40 g
Tare	Full	
Stabilisation time	2 ... 4 s	
Weighing units	kg or lb	
Maximum overload	125 %	
Check Weighing	With low and high limits	
Interface	RS-232 bi-directional interface	
Operating temperature	0° ... +40 °C	
Display	Backlit LCD with 35 mm digits with weight legends for kg, lb, low battery, stable, zero / 260 x 155 x 70 mm	
Power supply	- Internal rechargeable battery or - 12 VAC 150 mA from external mains adapter	
Calibration	Automatic external with calibration mass	
Housing	Indicator: Plastic Platform: Mild steel base and stainless steel pan	
Pan size	560 x 460 x 75 mm	
net weight	16 kg	

Delivery includes

1 x Platform Balance PCE-TS (Model PCE-TS 60 or PCE-TS 150), 1 x Weighing indicator (display) with 1 m cable, 1 x 800 mm steel pillar, 1 x Mains adapter, 1 x Weighing pan, User manual

Optional

- Software & RS-232 data cable
- Thermal printer PCE-PB1 incl. data cable
- RS232 / USB adapter
- ISO calibration certificate
- Calibration weight



PCE Group oHG
Im Langel 4
D-59872 Meschede
Germany
Fon: (49) 0 29 03 976 99-0
Fax: (49) 0 29 03 976 99-29
info@pce-group-europe.com
www.pce-group-europe.com